



WE HAVE YOU COVERED

SYNTHETIC ROOF UNDERLAYMENT

HOUSEWRAP

FLASHING & SEAM TAPES

TEMPORARY ROOF PROTECTION

REX SynFelt® is a high strength woven synthetic roof underlayment that can save you 50% in labor and time expense, compared to 30# felt.

- Slip resistant walking surface AND back surface – additional grip with two sided slip resistance
- 20 times stronger than asphaltic felt – won't tear off, buckle or curl when wet
- UV resistant and can be left exposed for up to 6 months
- Limited lifetime warranty – exceeds the needs of any final roof covering
- Pre-printed nailing pattern and overlap lines speeds installation



REX SynFelt®

PRODUCT SPECIFICATIONS		TEST METHOD	
Roll Width		48 in.	
Weight Per Square		2.8 lbs.	
Warranty		Lifetime	
Water Transmission		Pass	ASTM D-4869
Tensile Strength	MD	222 lbs.	ASTM D-5034
	CD	225 lbs.	
Tear Strength	MD	30 lbs.	ASTM D-4533
	CD	28 lbs.	
Pliability		Pass	ASTM D-226
Water Ponding		Pass	ASTM D-779

ROLL SIZE (ROLLS PER PALLET)	
48 in. x 250 ft. (35)	48 in. x 125 ft. (54)



WE HAVE YOU COVERED

TECHNO SB® ULTRA is a 100% synthetic woven roof underlayment offering high tear strengths including a slip resistant back side surface for added walking traction and a cool grey spunbond non-woven fabric walking surface.

- High Slip resistant back surface for added installation safety
- Non-woven walking surface with our AQUA TRAK® system
- UV resistant and can be left exposed for up to 6 months
- Lifetime warranty – guaranteed to shed water
- Pre-printed nailing pattern and overlap lines speeds installation

TEMPORARY ROOF PROTECTION
FLASHING & SEAM TAPES
HOUSEWRAP
SYNTHETIC ROOF UNDERLAYMENT



TECHNO SB® ULTRA

PRODUCT SPECIFICATIONS		TEST METHOD	
Roll Width		48 in.	
Weight Per Square		2.5 lbs.	
Warranty		Lifetime Warranty	
UV Exposure/Accelerated Aging		Pass	ICC-E S AC48
Tensile Strength	MD	155	ASTM D-5034
	CD	140	
Pliability		Pass - Type I & II	ASTM D-226
Liquid Water Transmission		Pass	ASTM D-4869
Fire Classification		Class A	ASTM E-108
Custom Printing	1 Color		1 Pallet Min.
	2 or 3 Colors		6 Pallet Min.

ROLL SIZE (ROLLS PER PALLET)	
48 in. x 250 ft. (42)	48 in. x 125 ft. (58)



Meets and exceeds all requirements of:
ICC-ES AC188
ASTM E108
ASTM D226 Type I & II

CODING LISTINGS
Intertek CCRR-0320

AlphaProTech Engineered Products, Inc.
301 South Blanchard St.
Valdosta, GA 31601
866-312-1837

Manufacturing & Distribution Facilities
Valdosta, Georgia
Nogales, Arizona
Salt Lake City, Utah





WE HAVE YOU COVERED

SYNTHETIC ROOF UNDERLAYMENT

HOUSEWRAP

FLASHING & SEAM TAPES

TEMPORARY ROOF PROTECTION

TECHNO SB® 50 is a 100% synthetic woven roof underlayment offering high tear strengths, including a tacky back-side slip resistant coating for added walking traction and a cool grey spunbond non-woven fabric surface.

- Non-woven walking surface with our AQUA TRAK System
- Slip resistant back surface for added installation safety
- UV resistant and can be left exposed for up to 6 months
- 50 year warranty – guaranteed to shed water
- Pre-printed nailing pattern and overlap lines speeds installation



TECHNO SB® 50

PRODUCT SPECIFICATIONS		TEST METHOD	
Roll Width		48 in.	
Weight Per Square		2.0 lbs.	
Warranty		50 Years	
Water Transmission		Pass	ASTM D-4869
Tensile Strength	MD	175 lbs.	ASTM D-5034
	CD	125 lbs.	
Pliability		Pass	ASTM D-226
Tear Strength	MD	45 lbs.	ASTM D-4533
	CD	24 lbs	
Nail Sealability		Pass	ASTM D-7349

ROLL SIZE (ROLLS PER PALLET)	
48 in. x 250 ft. (35)	48 in. x 125 ft. (54)



CODE LISTINGS
International Code Council
ICC ESR-1601
Florida Building Code
FL# 12512

AlphaProTech Engineered Products, Inc.
301 South Blanchard St.
Valdosta, GA 31601
866-312-1837

Manufacturing & Distribution Facilities
Valdosta, Georgia
Nogales, Arizona
Salt Lake City, Utah





WE HAVE YOU COVERED

SYNTHETIC ROOF UNDERLAYMENT

HOUSEWRAP

FLASHING & SEAM TAPES

TEMPORARY ROOF PROTECTION

TECHNOply® is a 100% synthetic woven roof underlayment offering high tear strengths, a proprietary walking surface and most important a green solution to today's ecological building technology. **TECHNOply®** is the **GREEN** answer to asphaltic felt paper.

- Manufactured from post industrial recycled materials
- 25 times stronger than asphaltic felt papers
- UV resistant and can be left exposed for up to 6 months
- 25 Year warranty - guaranteed to shed water
- Pre-printed nailing pattern and overlap lines speeds installation



REX TECHNOply®

PRODUCT SPECIFICATIONS		TEST METHOD	
Roll Width		48 in.	
Weight Per Square		2.0 lbs.	
Warranty		25 Years	
Water Transmission		Pass	ASTM D-4869
Tensile Strength	MD	217 lbs.	ASTM D-5034
	CD	198 lbs.	
Tear Strength	MD	35 lbs.	ASTM D-4533
	CD	36 lbs.	
Pliability		Pass	ASTM D-226
Nail Sealability		Pass	ASTM D-7349

ROLL SIZE (ROLLS PER PALLET)	
48 in. x 250 ft. (48)	48 in. x 125 ft. (60)

CODE LISTINGS
International Code Council
ICC ESR-1601
Florida Building Code
FL# 12512

AlphaProTech Engineered Products, Inc.
301 South Blanchard St.
Valdosta, GA 31601
866-312-1837

Manufacturing & Distribution Facilities
Valdosta, Georgia
Nogales, Arizona
Salt Lake City, Utah





WE HAVE YOU COVERED

TECHNO SB® 25 is a 100% synthetic woven roof underlayment offering high tear strengths including a slip resistant back side surface for added walking traction and a cool grey spunbond non-woven fabric walking surface.

- Slip resistant back surface for added installation safety
- Non-woven walking surface with our AQUA TRAK System
- UV resistant and can be left exposed for up to 6 months
- 25 year warranty – guaranteed to shed water
- Pre-printed nailing pattern and overlap lines speeds installation

SYNTHETIC ROOF UNDERLAYMENT
HOUSEWRAP
FLASHING & SEAM TAPES
TEMPORARY ROOF PROTECTION



TECHNO SB® 25

PRODUCT SPECIFICATIONS		TEST METHOD	
Roll Width	48 in.		
Weight Per Square	1.8 lbs.		
Warranty	25 Years		
UV Exposure/Accelerated Aging	Pass	ICC-ES AC48	
Tensile Strength	MD 93	ASTM D-5034	
	CD 86		
Pliability	Pass - Type I & II	ASTM D-226	
Liquid Water Transmission	Pass	ASTM D-4869	
Fire Classification	Class A	ASTM E-108	
Custom Printing	1 Color	1 Pallet Min.	
	2 or 3 Colors	6 Pallet Min.	

ROLL SIZE (ROLLS PER PALLET)	
48 in. x 250 ft. (42)	48 in. x 125 ft. (58)



Meets and exceeds all requirements of:
ICC-ES AC188
ASTM E108
ASTM D226 Type I & II

CODING LISTINGS
Intertek CRR-0320

AlphaProTech Engineered Products, Inc.
301 South Blanchard St.
Valdosta, GA 31601
866-312-1837

Manufacturing & Distribution Facilities
Valdosta, Georgia
Nogales, Arizona
Salt Lake City, Utah

