

TEMPORARY ROOF PROTECTION

FLASHING & SEAM TAPES

HOUSEWRAP

SYNTHETIC ROOF UNDERLAYMENT

WE HAVE YOU COVERED

REXTREME Window & Door Flashing



REXTREME Window & Door Flashing is a premium self-adhering butyl flashing that fulfills all requirements for AAMA 711 level 3, features a wide performance and application temperature range, and is suitable for applications below freezing. It shows excellent adhesion to OSB, brick, stucco and metal, as well as all common types of house-wrap. It can be used in connection with most sealants and will self-seal around nails. It is designed to stay flexible and will provide a tight water seal even in extreme weather situations.



REXTREME Window & Door Flashing

	PRODUCT SPECIFICATION	TEST METHOD
Color	White	
Thickness	15 mils	
Water Penetration Resistance	Pass (Initial)	AAMA 711-13
(Around Nails)	Pass (After Thermal Cycling)	ASTM D1970
90° Peel Adhesion		
Over OSB	Pass	AAMA 711-13
Over Aluminum	Pass	AAMA 711-13
Over Vinyl	Pass	AAMA 711-13
Over Plywood	Pass	AAMA 711-13
Tensile Strength	115	ASTM D5034 (lb/in) MD
	95	ASTM D5034 (lb/in) CD
Minimum Application Temp	18°F	AAMA 711-13
Elongation	620 % (At Break)	ASTM D5035
Tear Strength	38	ASTM D5587 (lbs)
Adhesion after Water Immersion	Pass	AAMA 711-13
Chemical Compatibility	Pass	AAMA 713
Resistance to peeling	Pass Level 3 @ 176°F	ASTM D3330
Peel/Heat Distortion	Pass Level 3	AAMA 711
Low Temperature Flexibility	Pass - no signs of cracking	ASTM D1970
Ultra Violet Light Exposure	120 days	

Roll Size (Rolls per Box)	
4"x75'	9 Rolls
6"x75'	6 Rolls
9"x75'	4 Rolls
12"x75'	3 Rolls

AlphaProTech Engineered Products, Inc.
 301 South Blanchard St.
 Valdosta, GA 31601
 866-312-1837

Manufacturing & Distribution Facilities
 Valdosta, Georgia
 Nogales, Arizona
 Salt Lake City, Utah



TEMPORARY ROOF PROTECTION

FLASHING & SEAM TAPES

HOUSEWRAP

SYNTHETIC ROOF UNDERLAYMENT

WE HAVE YOU COVERED

REX™ Premium Seam Tape



REX™ Premium Seam Tape is a high strength PET film designed for the toughest conditions with great cold and warm weather applications.

- Formulated with a “quick-tack” adhesive to speed installation
- 3” wide versus standard 2” wide tapes – more surface area to cover seams
- Easy quick tear edges to speed installation
- Excellent initial and long term adhesion
- Excellent chemical and thermal stability



REX™ Premium Seam Tape

PROPERTY TESTED	RESULTS
Backing	Polyester (PET)
Adhesive Material	High Tack Acrylic
Thickness	3.38 mil.
Adhesion (Peel)	60.0 oz./in.
Tensile Strength	< 20 lbs./in. width
Color	White
Roll Width	3 in.
Roll Length	165 Lineal Feet
Service Temperature	-22°F to 148°F
Application Temperature	-4°F to 105°F

Shelf Life: Recommend one year from date of receipt by customer when stored under optimum conditions. (70°F, 50% RH) Note: To the best of our knowledge, these are typical property values and are intended as guides only, not as specification limits. **ALPHA PROTECH ENGINEERED PRODUCTS, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO,** no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage.

AlphaProTech Engineered Products, Inc.
301 South Blanchard St.
Valdosta, GA 31601
866-312-1837

Manufacturing & Distribution Facilities
Valdosta, Georgia
Nogales, Arizona
Salt Lake City, Utah

